



SPEC

GLAZED SCREENS (Natural Speech)

(Ref: SU)

USE

Suitable for fitting to client supplied counter or in client prepared opening. Compatible for assembly in multiples and with other standard KS Security Ltd. supplied units.

APPLICATIONS

Cash Offices, Ticket Offices, Enquiry Windows, Reception Windows, Dispensary Windows, Surgeries

Not suitable for external applications

SPEECH

Natural speech transfer through mullions
(Also available for use with electronic speech enhancement systems)

PRODUCT CODE	UNIT SIZE (mm)			REQUIRED APERTURE (mm)	
	width	height	depth	width	height
SU1	1000	1050	76	1010	1060
SU2	1150	1050	76	1160	1060
SU3	1200	1050	76	1210	1060
SU4	1350	1050	76	1360	1060
SU5	1150	1250	76	1160	1260
SU6	1200	1250	76	1210	1260
SU7	1350	1250	76	1360	1260

LEVEL OF PROTECTION

Physical attack resistant
(Bullet resistant options available on request)

GLAZING MEDIUM

11.5mm 5 ply laminated glass, arbokoled into stainless steel channels to all 4 sides

MATERIALS

Frame - fully welded mild steel polyester powder coated goosewing grey, to BS 00 A 05, pre drilled fixing holes

APERTURE SIZE

For details see table

BESPOKE SIZES AVAILABLE ON REQUEST