


VERTICAL SLIDING HATCH

VH



VERTICAL SLIDING HATCH

USE

To protect staff & valuables from attack

APPLICATIONS

Cash Offices, Ticket Offices, Enquiry Windows, Reception Windows, Dispensary Windows, Surgeries

Not suitable for external applications

SPEECH

Natural speech transfer through mullions

TRANSFER

Packages
Clear pass - see table

LATCH STOP OPERATION

Locking at 100mm, 200mm & 300mm.
Slam down override

LEVEL OF PROTECTION

Physical attack resistant

GLAZING MEDIUM

11.5mm 5 ply laminated glass

MATERIALS

Frame - fully welded mild steel polyester powder coated goosewing grey, to BS 00 A 05, pre drilled fixing holes

APERTURE SIZE

See table

PRODUCT CODE	UNIT SIZE (mm)			REQUIRED APERTURE (mm)		CLEAR PASS (mm)	
	width	height	depth	width	height	width	height
VH1	490	1055	78	500	1065	400	435
VH2	560	1055	78	570	1065	470	435
VH3	560	1255	78	570	1265	470	535
VH4	710	1055	78	720	1065	620	435
VH5	710	1255	78	720	1265	620	535
VH6	710	1455	78	720	1465	620	535
VH7	820	1555	78	830	1565	730	670